

1

SAFETY DATA SHEET

CARBON DIOXIDE in non-refillable gas cylinders

Page: 1 of 5

First edition: September 2013

Last modified: October 2013

ICO.SD.001.e, Issue 03

Identification of the substance/mixture and of the company/undertaking

Product identifier			
Trade name	: Carbon dioxide in non-refillable gas cylinders		
Safety data sheet no.	: ICO.SD.001.e.03		
Chemical description of gas	: Carbon dioxide CAS-No.: 000124-38-9 EC no.: 204-696-9 Index no.:		
Chemical formula	: CO ₂		
UN number	: UN 1013		
REACH registration number	: CO ₂ is listed in Annex IV/V of regulation no. EC 1907/2006 (REACH). Exempted from registration.		
Usage	: For various industrial applications Perform risk assessment prior to use.		
Company name	: iSi Components GmbH Website: www.isi.com/components Kürschnergasse 6A E-mail: ico@isi.com A-1217 Vienna, Austria Tel.: +43 1 25099-803		
Emergency telephone number	: Poison information hotline Tel.: +43 1 406 43 43		

2 Hazards identification

Classification of the substance or mixture		
Classification according to EC 1272/2008 (CLP, GHS)	: Gases under pressure - Liquefied gas Contains gas under pressure; may explode if heated.	
Classification according to EC 67/548 and EC 1999/45	: Not classified as hazardous to health. No EC labeling required.	
Label elements		
Labelling regulation EC 1272/2008 (CLP):		
Hazard pictograms	\diamond	
 Signal word Hazard statements Precautionary statements 	 Warning H280: Contains gas under pressure; may explode if heated. P102: Keep out of reach of children. P403: Keep in a well-ventilated place. P410: Protect from direct sunlight. 	
Other hazards		
Other hazards	 May cause asphyxiation in high concentrations. Contact with solid CO₂ (dry ice) or liquid CO₂ may cause cold burns/ frost bite. 	



Page: 2 of 5

First edition: September 2013

Last modified: October 2013

CARBON DIOXIDE in non-refillable gas cylinders

ICO.SD.001.e, Issue 03

Substance/Preparation	: Substance				
Substance name Carbon dioxide	CAS no. 124-38-9	EC no. 204-696-9	Index no.	Registration no. See NOTE	Classification
					Liq. gas (H280)
Does not contain any other con Note: Listed in Appendix IV/V For full text of R-sets, se	REACH, exempt 1			he classification o	f this product.
First-aid measures					
Inhalation	mobility/ co Low concer Immediately made to we	 High concentrations can cause asphyxiation. Symptoms can include loss of mobility/ consciousness. Victim may not be aware of asphyxiation. Low concentrations of CO₂ cause accelerated breathing and headaches. Immediately remove victim to uncontaminated area. The victim should be made to wear respiratory equipment. Keep victim warm and rested. Call a doctor. Attempt artificial respiration if the victim stops breathing. 			
Contact with skin/eye	Spray any o	: Immediately flush eyes thoroughly with water for at least 15 minutes. Spray any cold burns immediately with water for at least 15 minutes. Cover with a sterile dressing. Consult a doctor.			
Ingestion	: Ingestion is	not seen as	s a possible i	method of exposu	re.
Fire-fighting measures					
Specific risks	: Non flamma Exposure to		ause cylinder	to burst/explode.	
Hazardous combustion Products	: None.				
Extinguishing media - Suitable extinguishing agen	nt : All known e	extinguishan	ts can be us	ed.	
Specific methods	: Move away	from cylind	er and cool v	vith water from a s	afe position.
Special protective equipment fire fighters	t for : In confined	spaces use	self-contain	ed breathing appa	ratus.
Accidental release measure	S				
Personnel-related precautions	: Ensure ade	quate ventil	ation.		
Environmental precautions		m entering s			ork pits or any other



Page: 3 of 5

First edition: September 2013

Last modified: October 2013

CARBON DIOXIDE in non-refillable gas cylinders

ICO.SD.001.e, Issue 03

7	Handling and storage	
	Handling	 Only use equipment suitable for this product and its pressure and temperature specified. If in doubt, consult iSi Components GmbH. Never use direct flame or electrical heating devices to raise the pressure of a cylinder. Never attempt to refill an empty cylinder. Emerging gas will cause the cylinder to freeze. Do not touch a discharging or recently discharged cylinder with bare hands. Never attempt to transfer gases from one cylinder to another. Do not use cylinder as roller or support, or for any other purpose than to contain the gas as supplied. Do not subject cylinder to mechanical shocks which may cause damage to their integrity.
	Storage	 Keep out of reach of children. Store cylinder in a well-ventilated place at less than 50°C. Store cylinder in a location free from risk of fire and away from sources of heat and ignition. Periodically check cylinder for general conditions and leakage. Do not store cylinder in conditions likely to encourage corrosion.

8	Exposure controls/personal protection			
	Personal protection	: Ensure adequate ventilation. Protect eyes, face and skin from liquid splashes. Wearing of protective gloves is recommended.		
	Occupational exposure limits	: Carbon dioxide: ILV (EC) - 8 H - [mg/m ³] : 9.000 Carbon dioxide: ILV (EC) - 8 H - [ppm] : 5.000 Carbon dioxide: TLV© -TWA [ppm] : 5.000 Carbon dioxide: TLV© -STEL [ppm] : 30.000		

9 Physical and chemical characteristics

Physical state at 20°C Colour Odour Molecular weight Melting point [°C] Boiling point [°C] Critical temperature [°C] Vapour pressure at 20°C Relative density, gas (air=1) Relative density, liquid (water=1) Solubility in water [mg/l]	: Gaseous. : Colourless. : Odourless. : 44 : -56.6 : -78.5 : 31.0 : 57.3 bar : 1.52 : 0.82 : 2000
Flash point [vol.% in air]	: Non-flammable.
Other information	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.



Page: 4 of 5 First edition: September 2013

Last modified: October 2013

CARBON DIOXIDE in non-refillable gas cylinders

ICO.SD.001.e, Issue 03

10	Stability and reactivity	
	Hazardous decomposition products Chemical stability	: None. : Stable under normal conditions.
11	Toxicological information	
	Toxicological information	: There are no toxic effects known for this product.
12	Ecological information	
	Ecological effects information	: May contribute to the greenhouse effect when discharged in large quantities. Depending on the technical specification the chromate layer which protects the cylinder's zinc-plating, may contain chromium in the oxidation state of VI.
	Global warming potential [CO ₂ = 1]	: 1
13	Disposable considerations	
	General	 Do not discharge into any place where its accumulation could be dangerous. Release into the atmosphere in a well-ventilated place. Avoid releasing large quantities into the atmosphere. Consult your supplier if you require advice.
	Disposal methods	 Dispose of emptied cylinders only. Cylinders are made of recyclable steel and hence a valuable resource. Emptied cylinders should therefore always be recycled. Adhere to local waste regulations when disposing of emptied cylinders. Never dispose of cylinders in an uncontrolled manner (e.g. dumping at sea).
14	Transport information	
	Land transport	: In accordance with the requirements set out in the current issue of the ADR
	Sea transport	: In accordance with the requirements set out in the current issue of the IMO-IMDG code
	Air transport	: In accordance with the requirements set out in the current issue of the IATA, Dangerous Goods Regulations.



CARBON DIOXIDE in non-refillable gas cylinders

Page: 5 of 5

First edition: September 2013

Last modified: October 2013

ICO.SD.001.e, Issue 03

15 Regulatory information

Safety, health and environmental regulations/ legislation specific for the substance or the mixture	: All national/local regulations apply.
Seveso regulations 96/82/EC	: Not covered.

16 Other information

Can cause asphyxiation in high concentrations. Keep cylinder in a well-ventilated place. Do not inhale the gas. Contact with liquid may cause cold burns/frost bite. The hazard of asphyxiation is often overlooked and must be stressed during operator training.

This safety data sheet has been produced in accordance with the applicable European directives. It applies to all countries which have adopted these directives as part of their national legislation.

DISCLAIMER OF LIABILITY

The information contained in this document is based on the latest knowledge and does not constitute a contractual assurance of product qualities. Before the product can be used in any new process or trial, careful tests of the material compliance and safety should be carried out.

-----End of document-----